Discovering Haplotype Blocks in the Human Genome

Alessandro Rinaldo¹, Bernie Devlin², Larry Wasserman¹, Kathryn Roeder¹

Carnegie Mellon

http://www.stat.cmu.edu/~arinaldo


Department of Statistics, Carnegie Mellon University 2 Department of Psychiatry, University of Pittsburgh

Introduction

aplotype block is a set of closely linked alleles/markers a chromosome that, over evolutionary time, tend to be arited together.

Accurate identification of haplotype blocks is important

- produce new insights into the physical and evolutionary dynamics of human chromosomes
- prove useful for the genetic analysis of complex diseases.



Provide a statistical characterization of haplotype blocks



Develop a methodology to identify LONG haplotype blocks, which are apparently regions of evolutionary conservation

Data

Seattle SNPs http://pga.gs.washington.edu/

The data used in the analysis are freely available from :

The UW-FHCRC Variation Discovery Resource (SeattleSNPs).

- 1. The analysis considered only "fully ...c analysis considered only "fully sequenced" genes (at least 90% of the gene).
- SNPs with minor allele frequency less than 10% and/or not in Hardy-Weinberg equilibrium were discarded.
- Reported results are for the African American sample (24 subjects).



The haplotype sequences were estimated from the genotypes using PHASE: http://www.stat.washington.edu/stephens/phase.html

Statistical Formalization

Each SNP / is a Bernoulli random variable X_i with some probability $\rho > 50\%$ of producing the major

The haplotype corresponding to m SNPs is the binary random vector $\mathbf{X} = \{X_1, \dots, X_m\}$.

A haplotype block is a subset of $\{X_1,...,X_m\}$ formed by contiguous SNPs exhibiting strong linkage

In statistical terms, those SNPs possess a high multivariate correlation.


Entropy as a Measure of LD

Traditional measures of linkage disequilibrium only consider pairse comparisons between SNPs.

Shannon's Entropy provides a multivariate measure of linkage disequilibrium among SNPs.

Let $\pmb{\mathcal{X}}$ be a random vector taking on k values with probabilities p1,...,pk. The **entropy of** $\pmb{\mathcal{X}}$ is:

$$H(\underline{X}) = -\sum_{i=1}^k p_i \log_2(p_i)$$



The *normalized entropy* and model selection procedure

Rather than using the raw entropy, the following entropy-based measure of LD seems to be more interpretable: the

$$0 \le 1 - \frac{H(\underline{X})}{\sum_{i} H(X_{i})} < 1$$

Values of the normalized entropy close to 0 indicate lack of LD.

Values close to 1 are observed in presence of strong LD.

Regions containing SNPs with high values of the normalized entropy are likely to form a block or be part of a block

Identification of haplotype blocks is achieved through a model selection


The proposed algorithm allows for partitions (blocking schemes) of the gene into sub-regions that are classified as either in-linkage disequilibrium (blocks) or in-linkage equilibrium.

Blocks are modeled as **independent Multinomial binary vectors** and SNPs not included in blocks are modeled like **independent strings of Bernoullis**.

Each partition of the SNPs into blocked and non-blocked regions is treated as a descriptive model of the genomic region. The optimal blocking scheme is selected as the solution to an AIC-type mode selection procedure. A penalty is imposed for the model complexity. The loss function to minimize is:

$$-2\lambda(\hat{\mathcal{G}})+2a$$

The parameter d measures the statistical complexity of the model and can be related to the minimal number of mutations leading to



The number of possible blocking schemes grows very fast with the number of SNPs. The complexity of the searching procedure was reduced by designing a greedy iterative algorithm that accounts only for partitions corresponding to regions with high values of the *normalized*

Specifically, each set of contiquous SNPs with normalized entropies above a predefined threshold are treated as a unique block. Different values of the threshold correspond to different blocking schemes. Therefore, finding the optimal partition is equivalent to choosing an optimal value of the threshold.

An approximate solution is obtained from the greedy algorithm. This solution is then perturbed locally to refine the estimated block structure

Some results



